

YOUR PROTECTION

BY EXCELLENCE

MULTICOVER 960

THE PEARL OF WELDING MACHINES











Multicover 960 enables cost savings by easy self-doing of pallet covers of different sizes according to need from heat shrinkable polyethylene film rolls. Avoid the costly stock of various sizes.

Using Multicover 960 is easy and fast

- Begin the passage of 3 to 5 cm of the film between the sealing bars.
- Lower one of the levers to make a perfect welding of a 3 mm width seal using the adjustment of temporization according to the thickness of film.
- Set the meter to zero. Open the sealing bars then unroll the film at the exact desired length.
- Close the sealing bars to make a welding which will be next cover. No need to wait for the end of this sealing before cutting and using the cover.
- Cut the film by moving the sliding carriage knife and separate the cover by pulling it slightly.

The non-return, eccentric rollers maintain film in position.

The dispenser Multicover 935 allows using up to 5 reels simultaneously. With the casters the set becomes completely mobile.

TECHNICAL SPECIFICATIONS

Item Code
Sealing method
Power supply
Cutting process
Maximum sealing capacity
Maximum admissible roll

N°349025
Adjustable electrical impulse
230V (50/60 Hz) - 24V . 0.5kVA
Sliding knife
4 x 150 µ / width 1440 mm
Ø 500mm - width 1440mm 220,46 lb - 100kg

Length/Width/Height 1920 x 600 x 1280 mm 75,6" x 23,6" x 50,4"

 Weight
 205 lb - 93 Kg

 Maximum charge
 441 lb - 200 kg

 Package dimensions
 2150 x 750 x 1450 mm

84,65" x 29,53" x 57,09" **Package weight** 352,74 lb - 160 Kg

Package Wood case - delivered assembled

EQUIPMENT SOLD SEPARATELY



RIPACK 3000



TROLLEY 932+



CALPACK





